



LED Roofrack for Jimny Models JB74

Compatible with: Jimny JB64/JB74 (2018+) — 3-Door | Difficulty: Moderate | Time required: 90–120 minutes | Tools: Socket set, hex keys, Phillip head screw driver, spanners

What's in the Box



Front, Rear, Left and Right rails, 8 cross tubes, and the two integrated LED light bars.

- Front, Rear, Left and Right rack rails
- 8x flat aluminium cross tubes (1st–8th, labelled by hole count)
- 2x integrated LED light bars (fit into the front rail)
- 6x inner roof gutter support brackets (sits inside the roof gutter)
- 6x outer roof gutter support brackets (installed on the outside of the roof gutter)
- Hardware kit — M8x16 screws and M8x30 screws

Before You Start

- This is a two-person job — the assembled rack is large and not possible to lift solo on top of the Jimny.
- Lay out the Front, Rear, Left and Right rails plus all 8 cross tubes as labelled before you start.
- Leave every screw finger-tight until the full rack is assembled and squared up.
- Check your Jimny's rain gutters are clear and undamaged before fitting the brackets.
- The longest screws M8x30 are for the last step to install the outer support brackets.

Step-by-Step

- 1 Lay out all parts as labelled — Front, Rear, Left, Right rails, the two LED light bars, and the 8 cross tubes.

- 2 Fit the two LED light bars into the cutouts on the Front rail.



LED light bar seated in the front rail cutout.

- 3 Join Front + Rear + Left + Right rails using M8x16 screws to form the outer frame.




Corner joint detail, and the completed outer frame.

- 4 Fit the 8 flat aluminium cross tubes into the frame using M8x16 screws — work through them in order (1st: 8 holes, 2nd: 4, 3rd: 2, 4th: 4, 5th: 4, 6th: 2, 7th: 4, 8th: 6).



Cross-tube mounting point, and the completed rack with all 8 tubes fitted.

- 5 Fit the 6 inner support brackets to the rack using M8x16 screws — leave them finger-tight for now.



Inner support brackets fitted to the rack, and all 6 brackets installed.

- 6 With two people, lift the assembled rack onto the roof and position the brackets inside the rain gutters.

7 Fit the 6 outer support brackets using M8x30 screws, finger-tight.



Gutter supports clamped onto the roof rain gutter.

8 Once the rack sits square, level and centred, tighten every screw fully.



Finished install.

Tips & Notes

- Keep every screw finger-tight until the final step — tightening early makes alignment difficult.
- Check the rack sits level and centred on the roof before final tightening.
- Recheck all screws after the first 100 km of driving, especially on rougher roads.

Need Help?

We offer professional installation at our workshop.

WhatsApp us at **1-868-320-0088** to book.

www.thejimnyshop.com